W

A-4300

Zinc

FUNCTION: Designed to prevent vibration, noise, and metal to metal contact in application. Versatile, cost effective two-bolt style EPDM rubber lined clamp. Features easy closing mechanism. Age resistant lining designed specifically for plastic pipe applications. Low friction properties allow for expansion, contraction and easy sliding of pipe. Category II noise reduction according to DIN EM ISO 3822-1. Compliant for sound insulation design according to DIN 4109.

APPROVALS: Complies with Manufactures' Standardization Society (MSS) SP-58 & SP-69 (Type 12).

MATERIAL: Steel and EPDM Rubber Liner

Iron Pipe Size	Plastic Pipe Size	Specification Data				Rec.
		OD	RS	w	т	Max. Load (lbs.)
1/2	20mm	0.787	3/8	1 3/16	1/16	250
3/4	25mm	0.984	3/8	1 3/16	1/16	250
1	32mm	1.260	3/8	1 3/16	1/16	250
1 1/4	40mm	1.575	3/8	1 3/16	1/16	250
1 1/2	50mm	1.902	3/8	1 3/16	1/16	380
2	63mm	2.374	3/8	1 3/16	1/16	380
2 1/2	75mm	2.874	3/8	1 3/16	1/16	380
3	90mm	3.500	3/8	1 3/16	1/16	380
3 1/2	110mm	4.000	3/8	1 3/16	3/32	440
4	125mm	4.331	3/8	1 3/16	3/32	440
5	-	5.512	3/8	1 3/16	3/32	440

This specification sheet is for reference only. Aimco International Group Corp. reserves the right to make changes to the design without prior notice.

FINISH: Zinc Electro-Galvanized

2-BOLT RUBBER LINED CLAMP



